


Flexible Metallic Conduit With Sealing Cord Packing (YF-708)



GALVANIZED STEEL STRIP
SEALING CORD PACKING :
COTTON, NYLON, RUBBER
OR COPPER WIRE

**Increased tensile strength
*Also suitable for use as
ventilation ductings*

PACKING TYPE	PRESSURE RANGE	Vacuum Rating	Temperature
COTTON	Up to 15 PSI	Up to 15" Mercury	300 F
NYLON	Up to 15 PSI	Up to 15" Mercury	180 F
RUBBER	Up to 20 PSI	Up to 20" Mercury	180 F
COPPER	Up to 15 PSI	Up to 15" Mercury	1200 F



Square locked flexible metal hose, with sealing cord packing for increased pressure and vacuum rating.

Type	Trade Size	I.D. (mm)		O.D. (mm)		Min. Bending Radius (mm)	Meter/Coil
		Min.	Max.	Min.	Max.		
YF-70803	3/8"	12.3	12.8	15.6	15.8	60	50
YF-70804	1/2"	15.8	16.2	19.5	19.9	80	50
YF-70806	3/4"	20.8	21.3	24.7	25.2	100	30
YF-70810	1"	26.4	27.1	31.6	32.1	150	30
YF-70812	1-1/4"	35.0	35.5	40.0	40.5	180	20
YF-70814	1-1/2"	40.1	40.6	45.8	46.3	220	20
YF-70820	2"	50.5	51.2	57.3	58.0	250	15
YF-70824	2-1/2"	62.9	63.9	72.1	73.1	300	10
YF-70830	3"	77.0	78.0	87.0	88.0	350	10
YF-70840	4"	99.6	101.6	108.7	110.5	400	10

Flexible Metallic Conduit With Sealing Cord Packing offers good mechanical protection and high tensile strength for Industrial wirings, appliances, automotive wire and cable sleeving, machineries, wire conduits, and under floor applications.